

High performance and durability

Cutting Capacity

Miter angle		0°	45°
Form of materials		ø127mm (5")	ø127mm (5")
		H x W: 102 x 194mm (4" x 7-5/8") 70 x 233mm (2-3/4" x 9-1/8")	H x W: 115 x 103mm (4-1/2" x 4-1/16")
		H x W: 119 x 119mm (4-11/16" x 4-11/16")	H x W: 106 (4-3/16) x 106 (4-3/16)
		S x S: 137 x 137mm, T: 10mm (5-3/8" x 5-3/8", 3/8")	S x S: 100 x 100mm, T: 10mm (4" x 4", 3/8")

* with Abrasive cut-off wheel 355



Carry handle for easy transportation

Quick release vise

Adjustable guide plate provides three angle settings up to 45° left and right; 15°, 30°, 45°



203

Double Insulation

Continuous rating input	2,000W
Wheel Diameter	355 mm (14")
No Load Speed (RPM)	3,800
Dimensions (L x W x H)	500x280x620mm (19-3/4"x11"x24-3/8")
Net weight	13.7 kg (30.2 lbs)
Power supply cord	2.5 m (8.2 ft)

Standard Equipment: Abrasive Cut-Off Wheel, Hex Wrench

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan