

maktec®

by Makita®

Drill MT605, MT606, MT607 10mm (3/8")



MT605, MT606
Keyed Chuck Type

In-line design
brings drilling pressure in line with center of drill bit axis.

Rubberized soft grip

Longer service life of carbon brushes in forward rotation achieved by using newly designed motor

Forward/Reverse change lever (MT606, MT607)

Lock-on button for continuous operation

MT607
Keyless Chuck Type

Compact and lightweight, yet with enough power.



Photo : MT605

- Trigger switch with variable speed control function and F/R Change lever. (MT606, MT607)
- Ergonomically designed handle with rubberized soft grip provides more control and comfort.
- Keyless chuck for fast bit replacement. (MT607)
- Chuck capacity: 1.5-10mm (1/16"-3/8").

Standard Equipment:
Chuck Key (MT605, MT606)

Double Insulation

Variable Speed (MT606, MT607)

Reversing (MT606, MT607)

Carrying Case (MT607)

	MT605	MT606	MT607
Continuous rating Input	450W	450W	450W
Capacity	Steel: 10mm (3/8") Wood: 25mm (1")	10mm (3/8") 25mm (1")	10mm (3/8") 25mm (1")
No load speed (rpm)	3,000	0-3,000	0-3,000
Dimensions (L x W x H)	229x64x175mm (9"x2-1/2"x6-7/8")	229x64x175mm (9"x2-1/2"x6-7/8")	234x64x175mm (9-1/4"x2-1/2"x6-7/8")
Net Weight*	1.3kg (2.8lbs)	1.3kg (2.8lbs)	1.3kg (2.9lbs)
Power supply cord	2.0m (6.6ft)	2.0m (6.6ft)	2.0m (6.6ft)

85

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan