

High rotation speed of 2,000rpm for user to do polishing applications comfortably.

MT620X : No drill chuck

is equipped so that a polishing attachment commonly used for India can be attached to the spindle.



Spindle size:
1/2"-20UNF

360° rotational side grip.

Maneuverable housing

- Easy to push the rear handle on your belly
- Easy to push the center axis of the machine



MT620: 13mm Keyed chuck



Double Insulation

	MT620X	MT620
Continuous rating Input	580W	580W
Capacity	Steel : 13mm (1/2") Wood : 25mm (1")	Steel : 13mm (1/2") Wood : 25mm (1")
Spindle size	1/2"-20UNF	-
No load speed (rpm)	2,000	2,000
Dimensions (L x W x H)	239x69x178mm (9-3/8"x2-3/4"x7")	283x69x178mm (11-1/8"x2-3/4"x7")
Net Weight*	1.7kg (3.7lbs)	2.0kg (4.4lbs)
Power supply cord	2.0m (6.6ft)	2.0m (6.6ft)

64 

Standard Equipment : Side Grip, Chuck Key(MT620), Wrench (MT620X)

Note: The polishing attachment and grinding wheel are not available from Makita. Prepare 1/2-20UNF thread of commercial polishing attachment and the grinding wheel.