Wide range of accessories available for various applications

Please see "Accessories for Multi Tool" for detailed information on the shape, size, recommended use and material of each blade.

Cutting (plunge cutting)







10



Sanding





Removing grout/ Cutting tiles



Scraping







BL1830:

18V 3.0Ah







BL1815: 18V 1.3Ah

BL1430: BL1415: 14.4V 3.0Ah 14.4V 1.3Ah









Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN BC-AG



....



Wide selection of accessories available for various applications





pplications: eplacing broken wall or floor tile.

Senefits: Less amount of dust scattering thanks to oscillating action. The segment shape allows flush cutting

Applications: Removing mortar, tile adhesive hardened glue, window putty, caulking, paint, etc.

Benefits: Low-profile blade with a narrow tip allows easy removal of caulking, window putty, etc.



Benefits: • Different from jig saws, etc, able to make a plunge cut in the wall for electrical connection box, lighting, exhaust fan, etc. The blade can be positioned in twelve different angles to allow easy operation in

Cutting of various materials such as oak wood, drywalls, plastics, copper pipes,

Applications:

tight spaces.

Applications:

of abrasive papers. Benefits:

• Able to sand in corners.

non-hardened nails, etc.

Applications Cutting of various materials such as oak vood, drywalls, plastics, copper pipes, on-hardened nails, etc.

Wood sanding, concrete sanding, or

paint removal, etc. with a variety range

Connectable to vacuum cleaner with

optional dust extraction system

 Able to perform long distance push cut. The segment shape allows flush cutting. Satisfy Professional's Needs



EXTRA VERSATILITY

Oscillating Multi Tool

RTM40

Compatible with all OIS (Oscillating Interface System) accessories



The standard equipment may vary by country.





Cutting metals





Cutting PVC, FRP pipes



Sanding and polishing various materials



Cutting tiles



Removing motar, tile adhesive

High operation efficiency

Oscillations per minute: up to 20,000 min⁻¹ Oscillating angle: 3.2°



Multi angle setting



Fully 360° multi angle setting enables users to position accessories in 12 different angles (each 30°) to allow access to tight spaces for optimum maneuverability.

Ergonomically best possible barrel grip

Thakita.

Anti-restart function prevents accidental startup.

Variable speed control by dial

Dust extraction system (Option)



Dust extraction system is available as an option for aggressive dust removal in applications with sanding pad.

Battery capacity warning lamp



Blinking red: Battery power is nearly used up. Solid red: Battery power is used up; battery protection circuit will shut off the power.



Routing joints on wall tiles










Cutting window putty, silicone



Cutting polystyrene, rubber











Metal flush cutting



Flush cutting of nails

Scraping floor tiles



Tankita Accessories for Multi Tool

Multi Tool Accessories Compatible with all OIS				
Multi Tool (option)	I Accessories	Compatible with all OIS (Oscillating Interface System) accessories		
Size: W= v	width (mm), L=le	ength (mm)		OIS
Sawing	Round and se	gment saw blades		
No.	Shape	Application/ Recommended Use	Dia. (mm)	Material of Blade
TMA001		Non-ferrous metal, FRP, PVC Suitable for corners.	85	BiM-TiN
TMA002		Non-ferrous metal, FRP, PVC Suitable for corners.	65	BiM-TiN
TMA003		Non-ferrous metal, FRP, PVC	85	BiM-TiN
TMA004	۲	Non-ferrous metal, FRP, PVC	65	BiM-TiN
TMA005		Wood&Metal Suitable for deep cutting	100	Bi-Metal
TMA006		Wood&Metal Suitable for flush cutting	85	Bi-Metal
TMA007		Wood Suitable for flush cutting	85	HCS

RIFF segment saw blades

No.	Shape	Application/ Recommended Use	Dia. (mm)	Material of Blade
TMA023		Routing joints on wall tiles	85	HM grit #30
TMA024	0	Routing joints on wall tiles For thiner joints 1/16"(1.6mm)	65	HM grit #50
TMA026		Routing joints on wall tiles Cutout of soft wall tiles and FRP	85	Diamond grit #40



Cutting PVC, FRP pipes

TMA001~TMA004



Cutting metals

TMA001~TMA006



Wood flush cutting

TMA005~TMA007







Accessories for Multi Tool

Plung-cutting saw blades

Flung-culling saw blades				
No.	Shape	Application/ Recommended Use	Size (W x L)	Material of Blade
TMA008		Wood and nails Suitable for plunge cutting	65 x 40	Bi-Metal
TMA009		Wood and Metal Suitable for deep plunge cutting in wood	28 x 50	Bi-Metal
TMA010		Hard Wood	32 x 40	Bi-Metal
TMA012		Wood	32 x 40	HCS
TMA013		Wood	20 x 30	HCS
TMA014		Wood	10 x 30	HCS
TMA015		Metal Suitable for flush cutting in nails or copper pipe	32 x 30	Bi-Metal
TMA016		Metal Suitable for flush cutting in nails or copper pipe	20 x 20	Bi-Metal
TMA017		Metal Suitable for flush cutting in nails or plasterboard	10 x 20	Bi-Metal





Deep plunge cutting

TMA008~TMA014



Metal flush cutting

TMA008, 009,015~017



Cutting plasterboards

TMA008~TMA017



Cutting copper pipe

TMA015, TMA016



Trakita Accessories for Multi Tool

Scraping	Scraper			
No.	Shape	Application/ Recommended Use	Size (W x L)	Material of Blade
TMA018		Removing mortar or tile adhesive	52 x 26	HCS
TMA019		Removing soft carpet adhesive residues or silicone joints	52 x 45	HCS

Cutting	Cutting blades				
No.	Shape	Application/ Recommended Use	Size (W x L)	Material of Blade	
TMA020		Polystyrene, Rubber Suitable for insulation material	100 Dia. (mm)	BiM	
TMA021		Cutting window putty or silicone	28 x 50	HCS	

Routing and Rasping		RIFF routing and removing blades		
No.	Shape	Application/ Recommended Use	Dia. (mm)	Material of Blade
TMA022	0	Removing grout or mortar Routing joints on floor tiles	70	HM grit #40

Riff sanding plate				
No.	Shape	Application/ Recommended Use	Dia. (mm)	Material of Blade
TMA025	0	Removing motar or tile adhesive	78	HM grit #30



Removing motar, tile adhesive TMA022, TMA025 Scraping floor tiles TMA018, TMA019





Cutting polystyrene, rubber

TMA020, TMA021



TMA019~TMA021

Cutting window putty, silicone





Corner cutting

TMA022



Trakita Accessories for Multi Tool

Wood / long-life

Suitable for sanding wood, hardwood, chipboard, construction boards and metal



Paper Size (mm)	Grit	Per pkg.	Part No.
93	60	10	B-21565
93	80	10	B-21571
93	100	10	B-21587
93	120	10	B-21593
93	180	10	B-21602
93	240	10	B-22931
93	60,80,100,120,180	10 (2pcs/each)	B-21559

Wood

Suitable for sanding wood and wooden materials



Paper Size (mm)	Grit	Per pkg.	Part No.
93	60	10	B-21624
93	80	10	B-21630
93	100	10	B-22947
93	120	10	B-21646
93	150	10	B-22953
93	180	10	B-21652
93	240	10	B-21668
93	60,80,120,180,240	10	B-21618

Paint

Suitable for sanding paint, varnish or roughcast



Paper Size (mm)	Grit	Per pkg.	Part No.
93	60	10	B-21680
93	80	10	B-21696
93	100	10	B-21705
93	120	10	B-22969
93	240	10	B-21711
93	320	10	B-21727
93	60,80,100,240,320	10 (2pcs/each)	B-21674

Stone

Suitable for coarse to gloss sanding of extremely hard materials such as stone or glass



Paper Size (mm)	Grit	Per pkg.	Part No.
93	120	10	B-21749
93	240	10	B-21755
93	400	10	B-21761
93	600	10	B-21777
93	1200	10	B-21783
93	120,240,400,600,1200	10 (2pcs/each)	B-21733

Fleece

Suitable for removing the rust of metal and the dirt of wood



Paper Size (mm)	Grit	Per pkg.	Part No.
93	100	1	B-21799
93	280	1	B-21808
93	without grit	1	B-21814
Polishing felt Suitable for pre-po			
		Der ska	Dout No.
Paper Size (mm)	Hardness rating	Per pkg.	Part No.
93	Hard	1	B-21820

Abrasive delta paper (hook & loop type) Use with Riff sanding pad





Part No. B-21537



Sanding and polishing various materials

Dust extraction system (Dust attachment set) Dust extraction system is available as an option for aggressive dust removal in applications with sanding pad.





