

# Cordless Ratchet Wrench DWR180 9.5 mm (3/8"), 6.35 mm (1/4")





# **Provides high speed fastening**





Max fastening torque

47.5<sub>N·m</sub>





#### Supplied with two socket adapters









9.5 mm (3/8") Part No.191A50-3

 $6.35 \, \text{mm} (1/4'')$ Part No.191A51-1



Can also be used as a hand ratchet wrench






50 an (18 V

#### Forward / reverse rotation change

Turn the reversing lever to the A side for clockwise rotation or to the B side for counterclockwise rotation.





#### Able to tighten 13mm nut onto M8 threaded rod

13mm nut only



#### Single LED job light

with preglow and afterglow functions



#### Tool bag

Part No. 832074-1





#### **Cordless Ratchet Wrench Series**





#### **Cordless Ratchet Wrench**

#### DWR180 9.5 mm (3/8")







Carrying Case

Capacity

Standard Bolt: M5 - M12 (3/16 - 1/2") High Strength Bolt: M5 - M10 (3/16 - 3/8") 9.5 / 6.35 mm (3/8 / 1/4") 0 - 800

47.5 N·m (420 in.lbs.)

Square Drive No Load Speed (RPM) Max Fastening Torque 2.5 m/s

Vibration Level Sound Pressure Level 74 dB(A)

Dimensions  $(L \times W \times H)$ 

w/o Battery: 350 x 79 x 67 mm (13-3/4 x 3-1/8 x 2-5/8") w/BL1815N/BL1820B: 369 x 79 x 69 mm

(14-1/2 x 3-1/8 x 2-3/4") w/BL1830B / BL1840B / BL1850B / BL1860B: 369 x 79 x 87 mm (14-1/2 x 3-1/8 x 3-7/16") 1.2 - 1.6 kg (2.6 - 3.5 lbs.)

Net weight Standard Equipment: Socket Adapter, Battery, Charger, Tool Bag (Country-specific)

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table.

### Items of standard equipment and specifications may vary by country or area.

## Makita Corporation